

---

INNOVATIVE  
DECKING  
SOLUTIONS



501.945.1919 • 888.450.DECK • 3912 E. Progress • N. Little Rock, AR 72114

Deckrite.com | 





## CHOICE

DeckRite is a durable, low-maintenance, flexible vinyl covering designed for applications on wooden or concrete decks, patios, balconies, breezeways, or any exterior walkway. It is slip-resistant, mildew-resistant, waterproof and engineered specifically for long-term performance. The membrane comes in five standard colors and is suitable for all climates.\*

## VALUE

DeckRite also acts as a waterproofing membrane which can be used on installations over living areas or on raised decks to keep the space below dry. It is also great for multiple deck applications on apartments and condominiums. No other product gives you more value for your dollar.



## INSTALLATION

Installation of the product is simple, clean and fast. DeckRite has a network of installers throughout North America. For do-it-yourselfers, our customer service department can help guide you through your DeckRite installation by providing all of the necessary materials to make your installation quick and trouble-free. This includes adhesives (water-based for wood, solvent-based for concrete), color coordinated, powder-coated aluminum termination bar, screws, and caulk. Hot air welding guns (for seaming) are available for rental. Installation DVD available upon request.

## MAINTENANCE

Traditional wood decks require the Rites of Spring: sanding, power washing, staining or sealing to keep them looking nice. With DeckRite, maintenance translates to little more than an occasional spray from the garden hose to keep the surface looking clean and new. DeckRite is resistant to staining from most household products. Make Spring a time for enjoyment.

## SERVICE

DeckRite offers a 7-year limited warranty against manufacturing defects. Please read the DeckRite warranty for details. Customer service at DeckRite is the lifeline to our customers. This attitude is paramount for every employee at DeckRite, who individually and collectively share the same commitment to servicing our customers.



## DeckRite 500 & 600 SERIES

DeckRite **500 Series** (50 mil, 3 Ply) & **600 Series** (60 mil, 3 Ply)

Physical Property	Unit	Test Method	DeckRite 500	DeckRite 600
<b>Color</b>			Tan, Gray, Marble, Cream, Sand*	Tan, Gray*
<b>Width</b>	Inches		68"	68"
<b>Length</b>	Yards		30 yds	30 yds
<b>Thickness</b>	Mils**	ASTM D751	50 mils (1.25 mm)	60 mils (1.5mm)
<b>Elongation (at break)</b>	w	ASTM D751	32	32
	f	ASTM D751	38	38
<b>Abrasion Resistance Tabor, cs10, 1000g. 1500 cycles</b>	Visual		Pass	Pass
<b>Low Temp Impact</b>	-22°F (-30°C)	ASTM D1790	Pass	Pass
<b>UV Exposure</b>	5000 hrs	ASTM G53	No Change	No Change
<b>Heat Aging</b>	7 days @ 158°F (70°C)	Visual	ASTM D751	No Change
				No Change
<b>Dimensional Stability</b>	DeckRite 600 %	DeckRite 600 CAN/CGSB 37.54-94	Mach Dir.	-0.08%
			Cross Dir.	-0.14%

Colors: Special Order Colors Available

Fade-Resistant: No appreciable color change after accelerated exposure of 5,000 hours using Weatherometer and/or FadeMeter.

This information is intended as a general specification guideline. Properties may vary from those stated or change without notice.

\* As with most exterior materials, colors may change with time. Check warranty details.

\*\*1 Mil = 0.001 inches

- Enhances the look of exterior walkways and decks
- Eliminates painting or staining wooden decks each year
- Can be applied to most surfaces
- Durable
- Slip-resistant
- Easy to install
- Easy to keep clean
- Waterproofing system
- Resists mildew, chemicals, and ultraviolet rays
- Eliminates the hazards of wood splinters and unsightly concrete spalling and cracking
- Complies with the ADA (Americans with Disabilities Act) for slip resistance

SAHARA TAN



SLATE GRAY



TUSCANY SAND



LAKEWOOD MARBLE



TROPICAL CREAM

